



## USD - Single Ended Metal Halide

- Compact Design
- High Brightness
- Daylight Color Temperature
- Universal Burn Position

[VIEW CATALOG](#)[PRINT VERSION](#)

### Additional Resources:

- [Product Data Specs Search](#)
- [Product Catalog](#)
- [Frequently Asked Questions](#)
- [Lamp Safety/Handling/MSDS](#)
- [Lamp Recycling Program](#)
- [Question about this Lamp](#)

- [TECHNICAL SPECIFICATIONS](#)
- [PHOTOS](#)

### TECHNICAL SPECIFICATIONS

Watts (W)	USHIO Ordering Code	USHIO Lamp Description	Volts (V)	Arc Gap	Dia. (mm)	LCL (mm)	OAL (mm)	Lum. Flux (lm)	Color Temp (K)	Ave. Life (h)	Base Type
250	5002003	USD-250/2	95	5	23	55	108	18000	8500	2000	GY9.5

Lamp contains Mercury. Manage in Accord with disposal Law s. See: <http://www.lamprecycle.org> or 800.895.8842

Specification is subject to change without notice.

### AVAILABLE PRODUCT PHOTOS



USR-575

### OTHER RELATED PRODUCTS:

- USR Series
- UMI Series

