



## USR - Single Ended Metal Halide

- Compact Design
- High Brightness
- Daylight Color Temperature
- Universal Burn Position

[VIEW CATALOG](#)[PRINT VERSION](#)

### Additional Resources:

- [Product Data Specs Search](#)
- [Product Catalog](#)
- [Frequently Asked Questions](#)
- [Lamp Safety/Handling/MSDS](#)
- [Lamp Recycling Program](#)
- [Question about this Lamp](#)

- [TECHNICAL SPECIFICATIONS](#)
- [PHOTOS](#)

### TECHNICAL SPECIFICATIONS

Watts (W)	USHIO Ordering Code	USHIO Lamp Description	Volts (V)	Arc Gap	Dia. (mm)	LCL (mm)	OAL (mm)	Lum. Flux (lm)	Color Temp (K)	Ave. Life (h)	Base Type
575	5000283	USR-575/BE	95	7	30	70	145	49000	5600	750	G22
575	5002008	USR-575/2	95	7	28	63	121	49000	7200	1000	GX9.5
700	5002010	USR-700SA	70	4	30	39	85	56000	5600	750	GY9.5
1200	5000278	USR-1200 HR	100	11	42	107	200	110000	5600	750	G38
1200	5002013	USR-1200/2	100	10	38.5	112	169	105000	7200	800	G22/ 30X53
2500	5000280	USR-2500 HR	115	14	60	127	240	240000	5600	500	G38
4000	5002014	USR-4000 HR	200	20	75	127	250	380000	6000	500	G38

Lamp contains Mercury. Manage in Accord w ith disposal Law s. See: <http://www.lamprecycle.org> or 800.895.8842

Specification is subject to change without notice.

### AVAILABLE PRODUCT PHOTOS



USR-575



USR-1200HR



USR-1200/2



USR-2500HR



USR-4000HR

### OTHER RELATED PRODUCTS:

- USD Series

- UMI Series

Copyright USHIO America, Inc. All rights reserved.